FILTER-LAB low ash qualitative filter paper

Ref. 1250
Code: PN1250055
Circles 55 mm. diameter **Box 100 units**

Filtration catalogue: pages 26, 27, 28, 29.

SPECIAL APPLICATIONS

- Analysis of beer and malt according to the paramaters recommended by EBC.
- Food testing.
- Soil analysis.
- Analysis of black smoke into the atmosphere according to the analyzer SF-8.
- Filtration of samples as calcium oxalate, magnesium phosphate, and some metal sulfides.
- Determination of total fat as some models of analyzers.
- Preparation of samples of fertilizers.
- Standard filtrations and clening of usual samples.

TECHNICAL SPECIFICATIONS

Reference	1250
Code	PN1250055
Diameter	55 mm.
Format	plain
Presentation	Box 100 units
Grammage (EN 536)	87 gr./m
Thickness (EN 20534)	0,180 mm.
Ash content (DIN 53137)	< 0,06%
Average pore size	10 - 13 µm
Filtration	Medium
Speed filtration (DIN 53137)	48 s
Bursting strengh resistance (ISO 2758)	> 5 kPa
Composition	Pure cellulose
Filter type	Depth filter

Related products

FILTER-LAB low ash qualitative filter paper

Made from cotton linter high purity. Analytical tests are used in critical qualitative.

Technical specifications

Ref.	Filtration / Thickness	Weight in grams g/m²	Thickness mm	Pore µm	Ash%
1248	Very quick	80	0.210	25 - 30	< 0.06
1249	Quick	80	0.180	20 - 25	< 0.06
1250	Medium	87	0.180	10 - 13	< 0.06
1252	Medium slow	80	0.160	7 - 9	< 0.06
1254	Slow	80	0.150	2 - 4	< 0.06
1256	Very slow	80	0.150	1 - 3	< 0.06
1258	Medium slow / thick	200	0.360	5 - 7	< 0.1

©2007 Filtros Anoia, S.A. All rights reserved

+34 93 899 50 36 fanoia@fanoia.com + 34 93 899 71 72