



FILTER-LAB® Non-woven fabric filters

Ref. NW 65 L

Code: PNNW65L150

Circles of 150 mm. diameter

box 100 units.



Filtration catalog: page 40.

SPECIAL APPLICATIONS

- Very fast filtration of samples with visible particles.
- Recovery of large particles of precious materials.
- Artificial insemination in cattle breeding.
- Harvesting of biological material in fish farms.
- Supports the production of traditional dairy products.
- Filtration of baby food or very dense samples in laboratories of the sugar industry (milk filters).
- Determination of the coefficient of water retention in the manufacture of gypsum.
- Pre-filtration filter paper before a finer retention.
- Determination of insoluble particles in a sample of sugar.

TECHNICAL SPECIFICATIONS

| | |
|------------------------------------------------------|---------------------------|
| Reference | NW 65 L |
| Code | PNNW65L150 |
| Size | 150 mm Ø. |
| Format | Flat disk |
| Presentation | Box of 100 units |
| Grammage (EN 536) | 65 gr./m ² |
| Thickness | 0,450 mm. |
| Air permeability pres. 200 Pa (UNE EN ISO 9237:1996) | 3910 l/m ² .s) |
| Average pore | 81 µm |
| Composition | Viscose |
| Type of filter | Depth |

Related products



Non-woven fabric filters FILTER-LAB

The non-woven filter made of synthetic fibers is very long, so linked together more or less regular by nature also synthetic resins. These filters are interesting features compared to other traditional type such as cellulose.

Technical Specifications

| Ref. | Weight gr/m ² | Thickness mm | Air permeability pressure 200 Pa l/(m ² .s) | Composition | Average pore diameter micras |
|---------|-----------------------------|-----------------|-----------------------------------------------------------|-------------|---------------------------------|
| NW 25 L | 25 | 0.215 | 5660 | Viscose | 206 |
| NW 35 L | 35 | 0.240 | 4785 | Viscose | 147 |
| NW 65 L | 65 | 0.450 | 3910 | Viscose | 81 |